

Indoor Speed Dome Camera



Features



- 35x or 22x optical zoom, 16x digital zoom
- Day & Night (option: IR-Cut filter Removable, ICR)
- On Screen Display (OSD) set-up menu
- 128 present points
- Remote Control via RS-485 (by RYK-8330 control keyboard)
- In-Ceiling or Surface installation application



• Surface



• In-ceiling



Embedded Mount

Controller :



RYK-8330
(RS-485)

Model No.	RYK-2E00	RYK-2E01	RYK-2E02	RYK-2E03
Image Device	1/4" Color Sony Super HAD (Hi-Res.)	1/4" Color Sony Super HAD	1/4" Color Sony EX-View HAD (Hi-Res.)	
Picture Elements	NTSC:768x494, PAL:752x582	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582	
Resolution	470 TVL	330 TVL	470 TVL	
Min. Illumination	0.7 Lux / F1.6	0.1 Lux (Night / BW), 0.3 Lux (Day / Color) / F1.6~3.7	0.01 Lux (Night / BW), 0.5 Lux (Day / Color) / F1.6~3.7	
Electronic Shutter	NTSC:1/60~1/30,000, PAL:1/50~1/30,000			
Lens Furnished	22x Auto Focus Zoom (3.9~85.8mm / F1.6~3.7)	22x (ICR) Auto Focus Zoom (3.9~85.8mm / F1.6~3.7)	35x (ICR) Auto Focus Zoom (3.6~126mm / F1.6~4.2)	
Digital Zoom Ratio	Basic 16x (Total Zoom Ratio 352x), 2x~16x variable			Basic 16x (Total Zoom Ratio 560x), 2x~16x variable
Zoom Speed	5 sec			8 sec
Focus Mode	Auto / Manual / Push Auto			
Iris Control	Auto / Manual			
White Balance	Auto / Hue / Indoor / Outdoor / manual / Push Auto			
Day / Night (ICR)	—	AE / Sensor / Day / Night		
Gain Control	Auto / Manual			
Back Light Comp.	On / Off			
Pan / Tilt	Angle	Pan: 360°, Tilt: 0°~90°		
Control	Speed Control	Manual: Pan 1°~150° / sec, Tilt: 1°~100° / sec, Auto: Pan 1°~300° / sec, Tilt: 1°~200° / sec		
Preset Point	128 preset points			
Sequence	6			
Remote Control	RS-485			
Compatible Protocol	YOKO / PELCO D&P / LG			
On Screen Display	Set-up menu			
Auto Turn Around	Yes			
Alarm / Relay	6 / 1			
Sync. System	Internal			
Video Output	1 Vp-p / 75 Ohms			
Power Supply	DC12V±10%			
Power Consumption	1083mA max.			
Operating Temp.	-10°C ~ 50°C			