

# ENTRY INDOOR DOME CAMERA

## Features


- 1/3" Color 960H CCD
- 700TVLines High Resolution
- High Sensitivity : 0.03Lux
- Sens-Up(x256) : 0.00019Lux
- Digital Noise Reduction (3DNR)
- Wide Dynamic Range (Digital)
- Dead Pixel Compensation
- Coaxial Communication



## Technical Specifications

Item	NTSC	PAL
<b>Imaging Sensor</b>	1/3" Color 960H CCD	
<b>Effective Pixels</b>	976(H) X 494(V)	976(H) X 582(V)
<b>Scanning System</b>	2:1 Interlace	
<b>Scanning Frequency</b>	H:15.734 kHz / V:59.94 Hz	H:15.625 kHz / V:50 Hz
<b>S/N Ratio</b>	More than 52dB (AGC Off)	
<b>Horizontal Resolution</b>	Horizontal : 700 TV-Line (Color)[Min] /800 TV-Line (B/W)[Min]	
<b>Video Output</b>	1.0 Vp-p (75Ω, Composite)	
<b>Min. Illumination</b>	Color : 0.03Lux(50IRE@F1.2) , 0.00019(Sens-up.256x)	
<b>Sync System</b>	Internal / Line Lock	
<b>O.S.D</b>	Available (Multi-Language Support)	
<b>Electronic Shutter Speed</b>	Auto / Flk	
	(NTSC : 1/60sec ~ 1/100,000sec)	(PAL : 1/50sec ~ 1/100,000sec)
<b>Gain Control</b>	Low / Middle / High / Off	
<b>Sens - up(Frame Integration)</b>	Off / AUTO (Selectable limit x2~ x256)	
<b>Backlight Compensation</b>	αWDR / BLC / HSBL / Off	
<b>White Balance</b>	ATB / AWB / AWC-SET / MANUAL	
<b>Lens</b>	3.6 mm Standard Fixed Lens	
<b>Day &amp; Night</b>	Color/ Auto / EXT / Night	
<b>Smart 3-DNR</b>	On / Off (Smart NR On/Off)	
<b>F-DNR</b>	Off / Manual / Auto	
<b>Motion Detection</b>	On / Off (4 Zone Selectable)	
<b>Privacy Masking</b>	On / Off (8 Zone Selectable)	
<b>D - EFFECT</b>	D-Zoom / Smart Dzoom / PIP / DIS / Free / Mirror / NEG.IMAGE	
<b>Image Adj</b>	Sharpness / Monitor / Lens Shading / Defect	
<b>Language</b>	English / Korean / Japanese / Chinese / Russian / French / Spanish Italian / portuguese / Dutch / German / Polish / Turkish / Hebrew / Arab	
<b>Supplied Voltage</b>	DC12 ±10%	
<b>Power Consumption</b>	100mA	

### ● Easy Installation with 3-Axis Ball Bracket



## Structure Specifications

MECHANICAL	
<b>Dimension</b>	112(Ø)X87mm
<b>Weight</b>	160g
ENVIROMENTAL	
<b>Operating Temp.</b>	-10 °C ~ 50 °C
<b>Storage Temp.</b>	0 °C ~ 50 °C
<b>Humidity</b>	0% to 90%

### ● Dimensions(mm)

