

Vandal-proof / Mini Dome Camera



Features


- Sony Super HAD CCD sensor
- Built-in Board Lens
- DC voltage





• Vandal-proof




• Normal mini



Vandal-proof



Normal mini



Model No.	Vandal proof	RYK-2J49	RYK-2J85	RYK-3J41	RYK-3J43
	Normal mini	RYK-2311	RYK-2385	RYK-3341	RYK-3343
Image Device		1/3" Color Sony Super HAD	1/3" Color Sony Super HAD (Hi-Res.)	1/3" B/W Sony Super HAD	1/3" B/W Sony Super HAD (Hi-Res.)
Picture Elements		NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582	EIA:510x492, CCIR:500x582	EIA:768x494, CCIR:752x582
Resolution		380 TVL	470 TVL	420 TVL	600 TVL
Min. Illumination		0.2 Lux / F2.0	0.3 Lux / F2.0	0.1 Lux / F2.0	0.2 Lux / F2.0
S/N Ratio		More than 48dB			
Electronic Shutter		NTSC:1/60~1/100,000, PAL:1/50~1/110,000		EIA:1/60~1/100,000, CCIR:1/50~1/110,000	
Gamma		0.45			
Lens Furnished		Board Lens 3.6mm / F2.0 (option:2.5/4.3/6/8/12/16mm)			
White Balance		Auto		-	
Gain Control		Auto			
Sync. System		Internal			
Video Output		1 Vp-p / 75 Ohms			
Audio Output		2 Vp-p / 50 Ohms (option, for RYK-2311/2385/3341/3343)			
Power Supply		DC12V±10%			
Power Consumption		117mA max.	110mA max.	100mA max.	108mA max.
Operating Temp.		-10°C ~ 50°C			

■ Series Model:

Model No.	Description
RYK-2335	1/4" Color Sony Super HAD, 330 TVL, 0.5 Lux
RYK-3363	1/3" B/W CCD, 400 TVL, 0.3 Lux