

# Weatherproof IR CAMERA

## Features

- 1000TVL, 1/3" Sony 1.3 Mega-pixel DIS
- 3.6mm Fixed IR Lens
- Removable IR Cut Filter
- Built-in 24 Leds
- IR Range: 15M (49.2ft)
- Viewing angle: Diagonal: 91 ° Horizontal: 71 ° Vertical: 54 °
- Feature: 3DNR
- 12VDC



## Technical Specifications

IP Rating	IP66
Type	Removable IR Cut Filter
Signal System	NTSC/PAL
Pick Up Device	1/3" Sony 1.3 Mega-pixel DIS
Picture Elements	NTSC:1280(H)X900(V) PAL:1280(H)X1024(V)
Resolution	1000TVL
Min Illumination	0Lux( 24PCs IR LED )
Vertical Frequency	NTSC:60Hz PAL:50Hz
Horizontal Frequency	NTSC:15.734KHz PAL:15.625KHz
Clock Frequency	NTSC/PAL:6MHz
Scanning System	2:1 Interlace
S/N Ratio	≥42dB
Lens	3.6mm Fixed IR Lens
Viewing Angle	Diagonal: 91 ° Horizontal: 71 ° Vertical: 54 °
White Balance	AUTO Tracking
Back Light Compensation	OFF
Auto Gain Control	OFF
OSD	YES
DNR	3DNR
GAMMA	0.45
Video Out-put	1V p-p,75Ω
Power Supply	DC12V ±10%
Current Consumption	260mA ( MAX )
IR Effect Distance	15m ( 49.2ft )
Dimension	155×79×69.4mm ( 6.1"×3.1"×2.7" )
Weight	380g
Storage Temperature	-30 ~ +60°C (-22 ~ +140°F )
Operating Temperature	-30 ~ +40°C (-22 ~ +140°F )

